

## Data Sheet

# Electrohydraulic Actuator

## Analog PVE Series 7

The PVE Series 7 is the newest actuator series to join the successful Danfoss PVE portfolio, which has evolved from a solid foundation of technical expertise dating back more than 40 years.

The Danfoss PVE platform offers customers fast, accurate and intelligent operation with plug-and-perform design and works in conjunction with Danfoss high performance proportional valves — PVG 32, PVG 100, PVG 120 and the new PVG 128 and PVG 256, as well as steering valves EHPS, EH, EHi and OSPE.

The PVE Series 7 seamlessly replaces PVE Series 4 actuators, while providing customers with all the new benefits.

The analog PVE Series 7 actuator program has a number of proven-in-use features that deliver the high reliability expected of a Danfoss Power Solutions product.



### Features

#### Benefits

- Increased robustness with new encapsulation standard and corrosion protection of metal parts
- Increased environmental capabilities with increased temperature range of -40 to +90 °C
- Enhanced event diagnostics with dual demodulator LVDT principle
- Increased power efficiency with the introduction of Power Save
- Improved EMC robustness with increased high frequency (HF) immunity field strength
- Easy to comply to on-road legislation with the introduction of the E-mark certificate
- Easier installation and service with new and more compact envelope design

#### Control Options

- Proportional actuators with multi-voltage 11-32 V<sub>DC</sub> supply voltage
- ON/OFF actuators with fixed 12 VDC or 24 VDC supply voltage
- Ratiometric input signal control
- Fixed 0-10 V<sub>DC</sub> input signal control (-U)
- PWM input signal control

#### Compliance and certification

- Compliant with European Directive 2004/108/EC
- Compliant with Machinery Directive 2006/42/EC
- E-mark certified acc. to UNECE regulation no. 10
- Certificates are available upon request

#### General

- Performance variants PVEO, PVEM, PVEA, PVEH and PVES
- Proportional closed loop control with integrated spool position feedback
- ON/OFF open loop control
- Integrated microcontroller with embedded software algorithms
- Event monitoring with active or passive event reaction and recovery
- Integrated LED indicating status
- Power Save
- Spool direction indication (-DI)
- Spool position feedback (-SP)
- Dedicated float pin (U<sub>F</sub>)
- Neutral Power-OFF (-NP)
- DEUTSCH, AMP and DIN/Hirschmann connector types

Comprehensive technical literature is online at [powersolutions.danfoss.com](http://powersolutions.danfoss.com)



**Technical data**

*Control specification*

Supply Voltage ( $U_{DC}$ )	PVEO	Rated	12 $V_{DC}$	24 $V_{DC}$
		Range	11 to 15 $V_{DC}$	22 to 30 $V_{DC}$
		Maximum ripple	5%	
	PVEM/A/H/S	Rated	11 to 32 $V_{DC}$	
		Range	11 to 32 $V_{DC}$	
		Maximum ripple	5%	
Signal Voltage ( $U_S$ )	PVEM/A/H/S	Neutral	$U_S = 0.5 * U_{DC}$	
		Q: P to A	$U_S = (0.5 \text{ to } 0.25) * U_{DC}$	
		Q: P to B	$U_S = (0.5 \text{ to } 0.75) * U_{DC}$	
	PVEH-U/PVES-U	Neutral	$U_S = 5 V_{DC}$	
		Q: P to A	$U_S = 5 V_{DC} \text{ to } 2.5 V_{DC}$	
		Q: P to B	$U_S = 5 V_{DC} \text{ to } 7.5 V_{DC}$	
Signal voltage PWM ( $U_S$ )	PVEM/A/H/S	Neutral	$U_S = 50\% \text{ DUT}$	
		Q: P to A	$U_S = 50\% \text{ to } 25\% \text{ DUT}$	
		Q: P to B	$U_S = 50\% \text{ to } 75\% \text{ DUT}$	
PWM Frequency ( $U_S$ )	PVEM	Recommended	>200 Hz	
	PVEA/H/S		>1000 Hz	

*Operating conditions*

Pilot pressure	PVEO/M/A/H/S	Nominal	13.5 bar	[196 psi]
		Minimum	10.0 bar	[145 psi]
		Maximum	15.0 bar	[218 bar]
	PVEO-HP	Nominal	25.0 bar	[363 psi]
		Minimum	21.0 bar	[305 psi]
		Maximum	25.0 bar	[363 psi]
Storage temperature	PVEO/M/A/H/S	Ambient	-50 to +90°C	[-58 to +194°F]
Operating temperature	PVEO/M/A/H/S	Ambient	-40 to +90°C	[-40 to +194°F]
Oil viscosity	PVEO/M/A/H/S	Operating range	12 to 75 cSt	[65 to 347 SUS]
		Minimum	4 cSt	[36 SUS]
		Maximum	469 cSt	[2128 SUS]
Oil cleanliness	PVEO/M/A/H/S	Maximum	18/16/13 (according to ISO 4406)	

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.